

KIENE

DIESEL ACCESSORIES, INC.

KIENE EUROPEAN-TYPE DIESEL ENGINE INDICATOR AND SAFETY VALVES



Kiene's 1715, 1720 and 1725 series indicator valves and 1750 series safety valves were developed and manufactured in Germany by Kistler/Baewert. They are designed for use on large, European diesel engines. In 2018, Kiene Diesel Accessories acquired these product lines from Kistler.

KIENE
DIESEL ACCESSORIES, INC.

Visit our website at www.kienediesel.com

E-mail: info@kienediesel.com

325 South Fairbank Street, Addison, Illinois, 60101 • Telephone: 1-800-264-5950 • Fax: 630-543-5953

1750 SERIES SAFETY VALVES FOR LARGE EUROPEAN DIESEL

Kiene's 1750 series safety valves were developed and manufactured in Germany by Kistler/Baewert. They are designed for use on large, European diesel engines.

In 2018, Kiene Diesel Accessories acquired these

DESIGN FEATURES

- 300 Bar Maximum Working Pressure.
- Relieves excess cylinder pressure.

ORDERING INFORMATION



DESCRIPTION	MODEL	OLD MODEL	ENGINE THREAD	OPENING
Safety valve 1750 M18x1.5	18028942	1200013	M18X1.5	Customer specified
Safety valve 1750 M22x1.5	18029236	1200019	M22X1.5	Customer specified
Safety valve 1750 G1/2	18028949	1200027	G1/2	200 bar
Safety valve 1750 G1/2	18028962	1200054	G1/2	125 bar
Safety valve 1750 G1/2	18033107	1200054	G1/2	150 bar
Safety valve 1750 G1/2	18032151	1200057	G1/2	80 bar
Safety valve 1750 G1/2	18029311	1200059	G1/2	175 bar
Safety valve 1750 G1/2	18029356	1200060	G1/2	206 bar
Safety valve 1750 G1/2	18030074	1200066	G1/2	100 bar
Safety valve 1750 G3/4	18031059	1200071	G3/4	250 bar
Safety valve 1750 M20X1.5	18032239	1200069	M20X1.5	Customer specified
Safety valve 1750 G1/2	18033792	-	G1/2	Customer specified
Safety valve 1751-22	18028943	1200014	G1/2	189 bar
Safety valve 1751-11	18028947	1200023	G1/2	135 bar
Safety valve 1751-20	18028955	1200042	G1/2	162 bar
Safety valve 1751-24	18028965	1200000	G1/2	241 bar
Safety valve 1751-19	18029808	1200064	G1/2	125 bar
Safety valve 1751-03	18032147	1200005	G1/2	125 bar
Safety Valve 1752 G1/2	18028954	1200041	G1/2	241 bar